



FACILITIES

by Tom Kolsun

Campus Buildings Need Verified Ventilation Performance

Humans breathe over 11,000 liters of air each day. Your staff and students will likely spend around 2000 hours per year breathing the air in campus buildings. As such, it's important to keep several facts about indoor air quality in mind. First, indoor air often contains 4X to 10X the amount of pollutants of outdoor air. Secondly, many studies have linked exposure to small particles (PM2.5—defined as airborne particles smaller than 2.5 microns) with heart attacks, cardiac arrhythmias, strokes, chronic obstructive pulmonary disease, worsened symptoms of asthma and an increased risk of respiratory illness.

Finally, the World Health Organization says that particulate matter contributes to about 800,000 premature deaths each year, making it the 13th leading cause of death worldwide.

Your Bottom Line and Student Performance

Employee wellness programs are great for employees and the university. The ability to reduce absenteeism and pre-absenteeism (working while sick) is the right thing to do and it goes directly to your bottom line. A study by Dominion Systems concluded that unscheduled absenteeism cost roughly \$3,600 annually for an hourly worker and \$2,650 for a salaried worker. Seems like a very compelling case for incorporating ventilation performance into your employee wellness program. Have it defined in your project; require Verified Ventilation Performance—VVP.

Now consider how verified ventilation performance (VVP) will increase productivity with your healthy employees and the positive

effects it could have on student learning. United Technologies and The Harvard School of Public Health conducted a study on the effects of indoor air quality on productivity. It demonstrated that lowering the levels of CO₂ and VOC's resulted in their participants scoring 61% higher on cognitive function tests compared with those in conventional offices. There was also a 101% improvement on their cognitive function tests when the ventilation levels were doubled above the standard ASHRAE prescribed levels. Additionally, information usage scores were 299% higher than conventional offices when the ventilation rates were doubled.

The conclusion of this study couldn't be more clear—verified ventilation performance will increase employee and student performance. Consider VVP in lecture halls, libraries and classrooms across campus. Better cognitive function means improving information retention, critical thinking and recall during exams.

Employees are paying attention more and more to the healthy conditions of their work environment. This is especially the case

for researchers and their lab environment. We see surging growth in universities adopting lab design programs such as Smart Labs which place an emphasis in the indoor environment quality of the lab and through certification programs as Green Globes, WELL Building, and WELCOA.

If your building design mandates verified ventilation performance, you are already contributing significantly to points required to attain these programs certifications, and you can use the VVP as a recruiting tool.

Building Ventilation

Let's look back a few decades and see how we got where we are with building ventilation. Most buildings design the core and shell with a set-it-and-forget-it strategy, which has been completed long before occupants ever arrive. I call this the 1970's Standard. Typically, this means that 80% of the indoor air is recycled. The percentage of ventilation air allowed in the facility is usually designed when the building is built and usually based on standard ASHRAE formulas.

The amount of ventilation air that comes in is frequently dependent on the position of a damper on the air handler. Ask anyone you know in the building automation business how

often they have experienced the actuators which control these dampers being broken. Oftentimes a building engineer has clamped the damper at a set position because the building was unable to maintain heating or cooling loads. Imagine it is a very hot and humid day. By reducing the ventilation air, the system isn't trying to cool 95-degree air (and dehumidify it). It only needs to cool air being returned from inside the building which has only gone up a few degrees above the building's set point. The same thing happens on cold days, with these values reversed.

The Challenge

There are actually buildings that run on 100% outside air. Research laboratories on campus are an example. All the air entering the building comes in from the outside, blows through the rooms and is immediately exhausted out. They are designed this way to dilute chemicals which are usually in fume hoods but may occasionally escape into the breathing zone. Why not demand all buildings mandate this type of HVAC system? The air would be fresh and clean all the time. It would be like standing outside on the roof of your building. Health and productivity would abound.

Here is why that won't work. The fans, cooling, heat and re-heat in lab buildings typically triple the first cost of the HVAC equipment of an ordinary building. Ongoing, they average 7 to 10 times the operating cost. As you can imagine, this will result in unattainable utility expenses.

Even if money were no object, the environmental impact of this strategy would be grave—which is why most energy codes do not allow for this. Please consider that buildings are the largest contributors to greenhouse gasses. In a 300,000 square foot non-critical space, running a standard HVAC system with 100% outside air would require an additional 27,580 MMBTU's. In layman's terms, your building would be adding 1686 Metric Tons of CO2 to the atmosphere every year—which would be the equivalent of burning 239,826 gallons of gas every year or adding 479 cars to the roads every year.

Financials and Mother Nature both preclude a standard HVAC system with the dampers set 100% open and no recirculated air for non-critical environments. Normal office occupancy is between 7 and 10 people per 1000 square feet. That leaves significant open spaces. And many times, people are congregated.

MANUFACTURING AMERICA'S FINEST PARK EQUIPMENT SINCE 1954

From speedy bleachers to picnic tables to bike racks and more



Kay Park Recreation

It Pays to Buy Kay's - "America's Finest" Since 1954

1-800-553-2476
www.kaypark.com

CREATING ENVIRONMENTS WHERE PEOPLE CAN SHINE™

**CONTROL
NATURAL LIGHT
& ILLUMINATE YOUR SPACE**

LIGHTWEIGHT, LIGHT DIFFUSING & EASY-TO-INSTALL
GUARDIAN 275® TRANSLUCENT PANEL SKYLIGHTS,
WALL SYSTEMS & CANOPIES

**MAJOR
INDUSTRIES**

SKYLIGHTS / CANOPIES / WALL SYSTEMS
MAJORSKYLIGHTS.COM
888-759-2678

Rooms and large portions of space are open. What if you have a system that would increase ventilation, but only where/when you need it?

The 1970's standard made a run at this. Using the best commercially available technology at that time, buildings were designed with some CO₂ sensors on the walls. The intention was to keep ventilation levels low and to increase outside air based on CO₂ levels. But here's the problem—brace yourself—air can be polluted by things other than CO₂. So, we build these airtight spaces, reduce the outside air as much as possible to save energy (and the environment) and either have a fixed amount of outside air or vary it based only on one potential contaminant not a recipe for a healthy and productive 2000 annual hours.

It's 2019. You're not carrying an analog bag-phone anymore. You need to have real time measurement of all the contaminants in your office air and match that with real time control of the outside air coming into your environment. You need a building that brings in lots of outside air—but only exactly where and when you need it—measures and controls more than just temperature and CO₂, and displays the ventilation performance for you, staff and students.

The Solution

It's 2019. This technology exists—just ask for it. You need to demand the new 2020 Ventilation Standard for your building. I highly recommend your project should require measured and verified ventilation that follows the criteria prescribed by the International WELL Building Institute, or some similar organization. They state that for optimal health, comfort and productivity the air in your space should remain at the following:

- Total VOC's—less than 500 ug/cubic meter
- Small Particles—(PM 2.5) to be less than 15 ug/cubic meter
- Relative Humidity—30% and 60%
- Carbon Monoxide—Below 9 PPM
- Carbon Dioxide—Below 750 PPM

Additionally, you need to be able to see it validated anytime on your computer or mobile device. Technology exists that can not only monitor these parameters but can actively control the ventilation rates to maintain high production/high health air. Many systems can also display this information with easy to understand graphics. You want staff, students and prospective employees to have full visibility to the great indoor environment you are delivering. This should be a marketing tool for attracting students and great talent.

You need to demand the 2020 Ventilation Standard as a part of your building projects for the health of your staff and students, for your recruiting and productivity, and for your bottom line.



ABOUT THE AUTHOR: Tom Kolsun is a Strategic Accounts Manager of Aircuity, Inc. where he is responsible for developing campus wide, airside efficiency programs for the largest operators of research space on the East Coast. Tom has over 25 years of experience in the building industry focused on systems serving commercial facilities with a primary focus on technical sales, system design, and project management.



LONGMEADOW HIGH SCHOOL

A+ In Economics

The XLERATOR high-speed, energy-efficient hand dryer helps schools around the world save time, money and the environment. It offers a 95% cost savings over paper towels, eliminating their labor, maintenance and waste while creating a more hygienic restroom. It's a lesson in green technology for your students and a sustainable solution for your school.

Make the change from paper towels today!



TIME TO THROW IN THE TOWEL®

888.891.3054
exceldryer.com
sales@exceldryer.com